



Dot Matrix Kitchen Printer





It prints on plain paper in three widths, offering print speeds of 4.7 lines per second and dual colour printing support. Designed for purpose, the Element RW337D provides a better performance and higher reliability with the following print head lifetime: 300,000,000 impacts, Cutter lifetime: 1.5 million cuts (Partial cut) 1.0 million cuts (Full cut) and a MCBF: 18,000,000 lines.

- > High print speed: 4.7LPS
- > Easy paper loading
- > Built-in power supply
- > Remove cutter error automatically
- > 64K receive buffer
- Anti paper jamming design
- > Paper saving function
- Support recording up time history and uploading the history record
- > Rich FEED button configuration function
- > Support 17 codepages



Technical Specifications - RW337D

| Item | | Parameter | | | |
|------------------------------------|---|--|---|--|--------|
| Print | Print Mode | 9-pin serial impact dot matrix | | | |
| | Print Width | Max.63.5mm or 400 (half dots) / 200 (full dots) | | | |
| | Resolution | 80 × 144dpi | | | |
| | Print Speed | Max. 4.7LPS (400 dots/line) | | | |
| Paper | Paper type | Continuous paper or marked paper | | | |
| | Single layer | Paper width:80±0.5mm 76±0.5mm 69.5±0.5mm, 57.5±0.5mm Paper thickness: 0.06 0.085m m | | | |
| | Multi layer paper (1 origi- nal+ 1 copies) | Paper width: 80±0.5mm 76±0.5mm 69.5±0.5mm, 57.5±0.5mm Paper thickness: 0.05 0.08mm (single page), total thickness ≤ 14 mm (total pages) | | | |
| Character | Character type | Font A: 9×9 Font B: 7×9 Chinese: 16×16 | | | |
| | Characters/line Default | | 80/76mm | 69.5mm | 57.5mm |
| | | Font A | 33 CPL | 30 CPL | 25 CPL |
| | | Font B | 40 CPL | 36 CPL | 30 CPL |
| | | Chinese | 22 CPL | 20 CPL | 16 CPL |
| | Character size (Default) | Font A: 1.6×3.1mm | 3.1mm Font B : 1.2×3.1mm Chinese: 2.7×2.9mm | | |
| | Characters/inch (Default) | Font A: 13.3CPI Font B: 16CPI Chinese: 8.9CPI | | | |
| Data buffer | Receive buffer | 64K /4K B/40bytes | | | |
| | NV bit image data area | 128KB | | | |
| | User NV memory | 8KB | | | |
| Ribbon specification | | ERC 38 ribbon cartridge | | | |
| Ribbon lifetime Buzzer | | ERC-38 (P) | | 4,000,000 characters | |
| | | ERC-38 (B) | | 3,000,000 characters | |
| | | ERC-38 (B/R) | | Black: 1,500,000 characters Red: 750,000 characters | |
| Communication interface | | USB / IEEE1284 / RS 232 / Ethernet interface | | | |
| Cash drawer connector | | 1~2 cash drawers | | | |
| Power supply | | DC 24V± 5 % average current 1. 5 A | | | |
| Reliability | | Printing Mechanism lifetime | | 10,000,000 lines | |
| | | Print head lifetime | | 150,000,000 characters | |
| | | Cutter lifetime | | 800,000 cuts (paper thickness:0.08mm, standard test condition) | |
| Operating temperature and humidity | | 5~45°C, 20~90%RH (40°C) | | | |
| Storage temperature and humidity | | -40~60°C, 20%~93% RH (40°C) | | | |
| Dimensions | | 160mm(W)×245mm(D)×154mm(H) | | | |
| Weight | | 3.0kg | | | |

