

Element P50BT

Cordless 2D Companion Scanner



The **Element P50BT** 2D companion scanner is designed to suit a wide range of applications to assist your mobile workforce. The Element P50BT has an anti-microbial casing, is designed for healthcare workflow with easy pairing with cradle, find-me function (vibrate/sound) and easy reset function to unbind and rebind with other cradles in your workplace environment.

Small, lightweight and easy to hold, the P50BT has a responsive scan performance with green line aiming, haptic feedback, night mode and offline batch mode. It is a feature rich solution to help your staff complete their mobile tasks.

The P50BT pairs directly with tablets or you can use the included Bluetooth charge/comms cradle (USB-HID / USB-COM Interface) to connect to existing workstations. It offers a 50m range and 2500mAh battery to provide long lasting mobile performance.

- > Stylish, rugged design
- > Low power consumption, strong performance
- > Reads all mainstream 1D/2D Barcodes
- > Fast barcode reading of a mobile phone screen
- > Anti-microbial
- > Bluetooth connectivity
- > Find-me functionality
- > Programmable vibrate function
- > Programmable outdoor high brightness scanning function

Technical Specifications - P50BT

Item		Parameter
Physical	Dimension (mm)	103mm x 50mm x 29mm
	Weight	162g
	Battery	2500mAh
Performance	Image (Pixels)	640 pixels (H)x 480 pixels (V)
	Light Source	Aiming: 617 nm LED; Illumination: 3500K white LED
	Field of View	4 ° (H) x 31° (V)
	Roll / Pitch / Yaw	360°, ±65°, ±60°
	Print Contrast	25% minimum reflective difference
	Screen Intensity	30%
Symbology	1D	UPC, EAN, Code128, Code 39, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Codabar, MSI Plessey, GS1 DataBar, etc.
	2D	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, etc.
	Motion Tolerance	up to 2m/s
User Environment	Operating Temperature	32° to 122° F / 0° to 50° C
	Storage Temperature	-40° to 158° F / -40° to 70° C
	Humidity	5% to 95%, non-condensing
	Drop Specifications	Withstands multiple 1.5m drops to concrete
	Ambient Light Immunity	Immune to normal indoor lighting up to 1600 Lux Immune to sunlight up to 86,000 Lux
Decode Ranges	5 mil (Code 39)	60mm - 155mm
	13 mil (100% UPCA)	50mm - 330mm
	1D Minimal Resolution	3mil
Features	Aiming	Green Line aiming for ease
	Night Mode	Turn on/off haptic feedback and LED
	Location	Single press button find-me feature
	Offline mode	Barcode configurable batch scanning in offline mode
	Connectivity	Directly pairs easily with Bluetooth devices (Windows/ IOS/ Android), or connects via Bluetooth Cradle
Warranty		24 Months
Performance may be impacted by bar code quality and environmental conditions		

* Specifications may change without notification (E&OE)