



## Epson TM-T88VI-iHUB

**Reliable, fast receipt printer with iHub connectivity, cloud and embedded server**

Ultra fast and versatile printing up to 350 mm/s

Built-in web server for custom web applications

Use as a peripheral hub for mPOS solutions

Connect to multiple devices and cloud servers

Triple interfaces including built-in USB and Ethernet

Print from web-based apps with ePOS print technology

Industry leading four year warranty

# Epson TM-T88VI-iHUB

## Product Specifications

<b>PAPER</b>		<b>GENERAL</b>	
<b>PAPER SIZE</b>	80 mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm 58 mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm	<b>PRODUCT DIMENSIONS</b>	145 x 195 x 148 mm (Width x Depth x Height)
<b>FONTS &amp; STYLES</b>		<b>PRODUCT WEIGHT</b>	1.6 kg
<b>PRINT SPEED</b>	350 mm/s	<b>COLOUR</b>	Black / White
<b>PRINT SPEED (DEFAULT)</b>	300 mm/s	<b>INSTALLATION</b>	Horizontally, wall hanging
<b>PRINTING FONT</b>	Font A (default): 12 x 24 Font B: 9 x 17 (including 2-dot horizontal spacing)	<b>INTERFACE CONNECTORS</b>	D.K.D. function
<b>COLUMN CAPACITY RECEIPT</b>	80 mm: 42/48/56 columns 58 mm: 30/36/40 columns	<b>HUMIDITY</b>	Operation 10% - 90%
<b>CHARACTER SIZE</b>	Font A: 1.41 x 3.39 (W x H mm) Font B: 0.99 x 2.40 (W x H mm)	<b>TEMPERATURE</b>	Operation 5 °C - 45 °C, Storage -10 °C - 50 °C
<b>CHARACTER SET</b>	95 Alphanumeric, 18 set International, 128 x 43 Graphic	<b>STANDARD COMPLIANCE</b>	
<b>PRINTING CHARACTERS</b>	Text (incl. Euro symbol), Graphics, Barcode	<b>SAFETY APPROVALS</b>	RCM: AS / NZS CISPR class A Energy-saving: ENERGY STAR
<b>INTERFACES</b>		<b>OTHER</b>	
<b>CONNECTIVITY</b>	Built-in USB, Built-in Ethernet (10/100Base-T/TX) +	<b>WARRANTY</b>	48 months
<b>CONNECTION TYPE</b>	USB type A connector x 1, USB type B connector x 4, RJ45 x 1, DB9 male x 1, DK x 1, 3 pin ,mini pin female x 1 Wireless (USB wireless dongle): OT-WL05 (802.11 a/b/g/n) or OT-WL02 (802.11 b/g/n) Beacon (using Bluetooth low energy): Beacon dongle (Epson approved dongle: Laird model BT-820)	<b>WHAT'S IN THE BOX</b>	
<b>DATA BUFFER</b>			Connector Cover
<b>DATA BUFFER</b>	45 Bytes or 4 kb, selectable		Main unit
<b>POWER</b>			PS-180 & AC cable
<b>POWER SUPPLY</b>	PS-180, AC cable		Paper spacer
<b>OPERATING VOLTAGE</b>	24 V		Power switch cover
<b>POWER CONSUMPTION</b>	Operating: 27.6 W Stand by: 0.5 W		Roll paper
			Setup guide
			Warranty document
		<b>OPTIONAL ACCESSORIES</b>	
		<b>C32C845040</b>	WH-10 (040) Wall hanging bracket
		<b>C32C890739</b>	OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz
		<b>C32C814596</b>	Power supply cover
		<b>COVER PLUS (OPTIONAL)</b>	
		<b>1YWT88VI-iHUB</b>	CoverPlus1 yr service pack TM-T88VI-iHUB

Better Products for a Better Future



Bluetooth™



Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

**EPSON AUSTRALIA**  
3 Talavera Road  
North Ryde NSW 2113  
Tel: 1300 361 054  
www.epson.com.au

**EPSON NEW ZEALAND**  
Level 2 7-9 Fanshawe Street  
Auckland, 1010  
Tel: 0800 237 766  
www.epson.co.nz

11/18

Epson CoverPlus

Fast. Reliable. Professional

**EPSON**  
EXCEED YOUR VISION